

## SMART BLACK PROJECTOR SCREEN PAINT

### APPLICATION GUIDE

Smart Black Projector Screen Paint is suitable for use on plaster, wallboards, wood, metal concrete and composites. For interior use only.

Each kit covers an area of 4.5m<sup>2</sup> / 48 sq. ft. This will create the following screen sizes:

120" or 279cm x 157cm (109.8" x 61.8") - at aspect ratio 16:9

All products within the Smarter Surfaces Projection Range have a certified gypsum Surface Finish Quality Standard of US 5/ EU Q4 guaranteeing a smooth, seamless surface ready for use with a high-quality projector for professional projection results.

## HOW TO APPLY SMART BLACK PROJECTOR SCREEN PAINT

1

### PREPARE THE SURFACE

- All surfaces to be painted should be clean, dry and free from loose materials.
- Measure the area you wish to paint and clearly mark it using masking tape.
- Prime bare, untreated surfaces with one coat of Smart White Primer.
- Once primed, lightly sand the surface.

2

### APPLY THE BASE COAT OF SMART BLACK PROJECTOR SCREEN PAINT

- Stir the projector paint thoroughly before use.
- For best results, apply paint using a mohair or lint free short pile roller sleeve.
- Apply 2 coats allowing the first coat to dry (approx. 2-4 hours at 20°), before applying the second coat.

3

### DRYING TIME

- Smart Black Projector Screen Paint will be touch-dry in 1-2 hours and usable after 24 hours.

### PRODUCT LIABILITY CLAUSE

The sale of our products is subject to our General Terms and Conditions available on [www.smartersurfaces.com](http://www.smartersurfaces.com)

### SUPPORT

EMAIL:  
[support@smartersurfaces.com](mailto:support@smartersurfaces.com)

PHONE (IRE):  
+353 1 412 6200

WEBSITE:  
[www.smartersurfaces.com](http://www.smartersurfaces.com)