

SMART AMBIENT LIGHT REJECTING PROJECTOR SCREEN PAINT

APPLICATION GUIDE

Smart Ambient Light Rejecting Projector Screen Paint is suitable for use on plaster, wallboards, wood, metal concrete and composites. For interior use only.

Each kit covers an area of 4.5m² / 48 sq. ft. This will create the following screen sizes:

120" or 279cm x 157cm (109.8" x 61.8") - at aspect ratio 16:9

All products within the Smarter Surfaces Projection Range have a certified gypsum Surface Finish Quality Standard of US 5/ EU Q4 guaranteeing a smooth, seamless surface ready for use with a high-quality projector for professional projection results.

HOW TO APPLY Smart Ambient Light Rejecting Projector Screen Paint

Smart Ambient Light Rejecting Projector Screen Paint is applied in one coat

1

PREPARE THE SURFACE

- All surfaces to be painted should be clean, dry and free from loose materials.
- Measure the area you wish to paint and clearly mark it using masking tape.
- Prime bare, untreated surfaces with one coat of Smart White Primer.
- Once primed, lightly sand the surface.

2

APPLY THE SMART AMBIENT LIGHT REJECTING PROJECTOR SCREEN PAINT

- Ensure the base is smooth and free from surface defects (lightly sand if required).
- Apply the first coat with a mohair or lint free short pile roller sleeve.
- Allow to dry before applying the second coat.

3

DRYING TIME

- Once all coats are applied Smart Ambient Light Rejecting Projector Screen Paint will be ready to use in 24 hours.

PRODUCT LIABILITY CLAUSE

The sale of our products is subject to our General Terms and Conditions available on www.smartersurfaces.com

SUPPORT

EMAIL:
support@smartersurfaces.com

PHONE (IRE):
+353 1 412 6200

WEBSITE:
www.smartersurfaces.com